

**PRESS RELEASE
FOR IMMEDIATE RELEASE**

**CUERVO REPORTS RESULTS FROM CONTINUING IRON ORE DRILLING
PROJECT IN PERÚ**

November 15, 2007 – Toronto, ON

Cuervo Resources Inc. (CNQ-IRON; FWB-CRR; “Cuervo” or the “Company”) wishes to announce additional results from the Company’s ongoing diamond-drilling program on its Cerro Ccopane iron ore project in Perú. The Cerro Ccopane property is located in southern Perú, 65 km to the south of Cuzco. Previous results were announced in press releases dated October 22nd, October 30th and November 1st 2007 and included intersections of up to 57.31% Fe over 131.25 m.

The program of diamond drilling by the Company’s wholly owned subsidiary Minera Cuervo S.A.C. (“Minera Cuervo”) is currently being focussed on the Orcopura (also known as Wychaucassa or Posada 2) zone of mineralization. Two diamond drills are now at work on the program. The Company is targeting near surface, relatively flat-lying iron mineralization (magnetite \pm hematite). The following list describes the general locations of the next four (4) drill holes being reported on:

ODH – 15, ODH – 16 and ODH – 17 were all drilled from the same location (platform), ODH - 15 being a vertical drill hole to a depth of 95 m, ODH – 16 being drilled toward grid north at an inclination of 45° to a depth of 128.25 m and ODH – 17 being drilled toward grid east to a depth of 195.40 m. The site was located 100 m to the (grid) west of previously announced holes ODH – 07 and ODH – 08. ODH – 15 was collared just outside the known limits of surface mineralization and did not encounter any mineralization at depth. No samples were taken from this hole for analysis. Elevation of the location is 3727 m AMSL; and

ODH – 18 was a vertical hole (total depth 106.75 m). This site was located at a point 100 m to the (grid) west of previously announced holes ODH – 01, ODH – 02 and ODH - 03. Elevation of the location is 3769 m.

Locations of the collars of the drill holes are tied to the Company’s orthophoto-topographic basemap by GPS surveying.

The following table presents a list of the significant intersections that were sampled during the recent work program:

DRILL HOLE	INTERSECTION (m)	LENGTH (m)	TVD (m)*	Fe (%)	S (%)	P (%)	Mn (%)	Cu (%)
ODH – 16	16.65 – 46.65	30.00	21	59.83	3.07	0.01	0.07	0.17
Other	66.15 – 90.15	24.00		57.60	3.35	0.02	0.08	0.11
Other	93.15 – 99.15	6.00		57.13	3.52	0.03	0.09	0.11
ODH – 17	17.00 – 29.00	12.00		54.40	2.76	0.01	0.09	0.14
Other	33.50 – 60.50	25.50	17	52.29	3.80	0.01	0.11	0.08
Other	72.40 – 80.10	7.70		57.13	4.77	0.01	0.10	0.07
Other	102.6 – 122.65	20.05		53.87	5.29	0.02	0.12	0.10
Other	157.65 – 180.0	22.35		54.07	4.03	0.03	0.09	0.11
ODH – 18	5.50 – 40.00	34.50	34	62.97	0.37	0.12	0.03	0.03
Other	78.15 – 82.65	4.50		55.94	3.12	0.02	0.13	0.05
Other	91.65 – 99.15	7.50		56.32	4.28	0.03	0.06	0.12

* TVD – approximate total vertical depth from top to bottom of intersection

All drill holes were logged and sampled at the property campsite on the property under the direction of Minera Cuervo's senior geologist, ing. Abraham Castillo Ll. A nominal sampling interval of 1.5 m is currently being used within sections of typical iron mineralization. Analyses were performed by SGS Minerals Services at their laboratory facilities in Lima (Callao), Perú. The reported Iron (Fe) analyses were determined by titration methods, sulphur (S) were carried out with a LECO furnace. All other reported analyses, which include phosphorus (P), manganese (Mn) and copper (Cu), were by performed ICP-AES after a multi-acid ("total") digestion. Laboratory check analyses were performed on approximately 10% of the samples submitted while field duplicate samples are submitted on a rate of approximately 5% of the total samples sent to the laboratory. The Company is satisfied with the reproducibility of analyses for the elements reported.

While the Company recognizes that certain elements, including sulphur, can have a debilitating effect on the quality of a potential iron ore product, at this stage the Company has no indications that this could be of consequence at this location. The sulphur is identified as being present as sulphide minerals, predominantly pyrite, in the Orcopura zone. The Company has selected samples for preliminary separate mineralogical and metallurgical (Davis Tube) studies to further assess the character of the iron mineralization. The results of these studies should be available to the Company in approximately two to four week's time. The Company has also commissioned a preliminary transportation study.

Exploration work and content of this release has been carried out under the supervision of Mr. John M. Siriunas, P.Eng., the designated qualified person for Cuervo under the definition of NI43-101.

The Company has 23,287,050 shares outstanding (33,716,000 fully diluted).

For further information, please contact Mr. Siriunas, a director and President of Cuervo, at 416-203-3957 x4700 or Mr. Tom Berner, Investor Relations, at 416-324-8322 x202. Additional information about Cuervo can be found at the Company's website at www.cuervoresources.com.

The Canadian Trading and Quotation System Inc. has neither approved nor disapproved of the contents of this press release.